



Spectrum

LED Emergency Slim/Standard Exit Sign

Slim Exit Sign (09000)

- Injection moulded profile
- Supplied with New Up Legend as standard
- Sleek, low profile design
- Suitable for Commercial and Industrial installations
- Maintained and Non Maintained
- 25M Viewing Distance
- Downward light feature
- Polycarbonate construction

Downward light feature: To illuminate points of emphasis, fire fighting equipment, call points, first aid points, safety signs and exit doors.



Auto Self Test Indicator. No requirement for manual key test.

Normal operation: Green indicator illuminated

Battery failure: Red indicator flashes once every 3 seconds

Light source failure: Red indicator flashes twice every 3 seconds

Less than rated duration time: Red indicator flashes three times every 3 seconds

09000 Legend Options



09001 New (ISO) Legend Reversible Left & Right



09003 New (ISO) Legend Down



09005 Old (Euro) Legend Reversible Left & Right



09007 Old (Euro) Legend Down



09008 Old (Euro) Legend Up

Standard Exit Sign (09019)

- Supplied with New Up Legend as standard
- Robust design
- Suitable for Commercial and Industrial installations
- Maintained and Non Maintained
- 25M Viewing Distance
- Downward light feature
- Steel construction

Downward light feature: To illuminate points of emphasis, fire fighting equipment, call points, first aid points, safety signs and exit doors.



09019 Legend Options



09020 New (ISO) Legend Left



09021 New (ISO) Legend Right



09022 New (ISO) Legend Down



09024 Old (Euro) Legend Left



09025 Old (Euro) Legend Right



09026 Old (Euro) Legend Down



09027 Old (Euro) Legend Up




Spectrum


Technical Specification

Data	
Construction	09000 Polycarbonate / 09019 Steel
LED Chip	Samsung
IP Rating	IP20
Operating Temp	-5°C to +35°C
Input Voltage	220-240V
Power Factor	> 0.9

09000 Slim Exit Sign



09019 Standard Exit Sign



Code	W	Description	Viewing Distance	Temp	Hours
09000	3	LED Emergency Slim Exit Sign including Up Legend. Maintained/Non Maintained	25M	6500K	25000
09001	-	New Legend Left + Right for Slim Exit Sign	-	-	-
09003	-	New Legend Down for Slim Exit Sign	-	-	-
09004	-	New Up Legend for Slim Exit Sign (spare accessory)	-	-	-
09005	-	Old Legend Left + Right for Slim Exit Sign	-	-	-
09007	-	Old Legend Down for Slim Exit Sign	-	-	-
09008	-	Old Legend Up for Slim Exit Sign	-	-	-
09019	4	LED Standard Exit Sign including Up Legend. Maintained/Non Maintained	25M	6500K	25000
09020	-	New Legend Left for Standard Exit Sign	-	-	-
09021	-	New Legend Right for Standard Exit Sign	-	-	-
09022	-	New Legend Down for Standard Exit Sign	-	-	-
09023	-	New Up Legend for Standard Exit Sign (spare accessory)	-	-	-
09024	-	Old Legend Left for Standard Exit Sign	-	-	-
09025	-	Old Legend Right for Standard Exit Sign	-	-	-
09026	-	Old Legend Down for Standard Exit Sign	-	-	-
09027	-	Old Legend Up for Standard Exit Sign	-	-	-

Must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty.



¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio
² Exceeds EU standard of RA 80 for Colour Rendering Index
³ Subject to terms & conditions (Contact Customer Service)