







## LED Emergency IP65 Twin Spot

The Spectrum IP65 Twin Spot is IP65 as standard. Supplied as both Self Test  $\theta$  Non Self Test, with 20mm side  $\theta$  rear entry and a 5 year guarantee.

- Long life & low maintenance
- · Compact design
- Robust Construction
- 20mm Side & rear entry











Auto Self Test Indicator. No requirement for manual key test (09089 Version).

Normal operation: Green indicator illuminated

Battery failure: Red indicator flashes once every 3 seconds Light source failure: Red indicator flashes twice every 3 seconds

Less than rated duration time: Red indicator flashes three times every 3 seconds.

Technical Specification				
Construction	Polycarbonate			
LED Chip	Samsung			
IP Rating	IP65			
Operating Temp	-5°C to +35°C			
Input Voltage	220 - 240V			
Power Factor	> 0.9			
Battery	LiFePO4			

Code	W	Description	Temp	Lm	Hours
09088	12	LED Emergency Twin Spot IP65. Non Maintained	6500K	550	30000
09089	12	LED Emergency Twin Spot IP65. Self Test Non Maintained	6500K	550	30000

## See end of Emergency Lighting section for spacing tables

Must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty.

