



# Ultrastlim

## LED Integrated Batten

- The smart replacement for Fluorescent Fixtures
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Cool white
- Quick and easy installation
- Shatterproof
- 3 year guarantee



Code	W	Description	Temp	lm	Hrs
10270	38	Ultra Slim LED Integrated - 4000K, Single 1230mm (4ft)	4000	4400	35000
10271	45	Ultra Slim LED Integrated - 4000K, Single 1530mm (5ft)	4000	5300	35000
10272	56	Ultra Slim LED Integrated - 4000K, Single 1850mm (6ft)	4000	6600	35000




<sup>1</sup> Exceeds EU standard of 70 for Lumens Maintenance Ratio  
<sup>2</sup> Exceeds EU standard of RA 80 for Colour Rendering Index  
<sup>3</sup> Subject to terms & conditions (Contact Customer Service)



# Ultralim

## Technical Specification

Data	
<b>Construction</b>	Aluminium Body, Polycarbonate lens
<b>Driver</b>	BELL
<b>LED Chip</b>	Samsung
<b>IP Rating</b>	IP20
<b>Operating Temp</b>	-30°C to +35°C / Emergency Version -10°C to +35°C
<b>Input Voltage</b>	220 - 240V
<b>Power Factor</b>	> 0.9
<b>CRI</b>	85 - Exceeds EU standard of Ra 80 for Colour Rendering Index
<b>LMR</b>	80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio
<b>ECA Compliant</b>	Yes
<b>L1A / L1B / L2A / L2B Compliant</b>	Yes



Model	A	B	D
<b>38W</b>	75mm	1230mm	26mm
<b>45W</b>	75mm	1530mm	26mm
<b>56W</b>	75mm	1850mm	26mm

