






## LED Ground Light

The Luna Ground Light offers a robust construction with a sleek modern design. Resin filled to prevent water ingress, the Luna LED Ground Lights are the perfect way to define boundaries and walkways, whether that be on a commercial property or domestic dwelling.

- Define the boundaries of your outside space
- Robust construction, withstands being driven over (Max 2000 Kg)
- Fully encapsulated in resin to prevent water ingress
- 50000 Hours
- Cool White
- 3W - 157lm / 6W - 300lm / 9W - 580lm
- 304 Stainless Steel
- Ensure safe passage of personnel
- No lamp changes - 'fit & forget'



|           | 3W     | 6W      | 9W      |
|-----------|--------|---------|---------|
| A         | 106mm  | 97mm    | 124mm   |
| B Ø       | 100mm  | 129mm   | 180mm   |
| Cut Out Ø | Ø 90mm | Ø 122mm | Ø 165mm |



technical@belllighting.co.uk  
sales@belllighting.co.uk



# LED Ground Light

## Technical Specification

|                |  |
|----------------|--|
| Construction   | Stainless Steel  |
| IP Rating      | IP67   |
| Input Voltage  | 220-240  |
| Operating Temp | -20°C to +35°C   |
| CRI            | 80 - Exceeds EU standard of Ra 70 for Colour Rendering Index |
| LMR            | 80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio  |

\* All BELL Lighting luminaires are rated L80 B10, so for a 50,000 hour product. L80B10 at 50,000 hours our fittings will still have 80% of initial lumen, only 10% of fittings may fail to achieve this

| Code  | W | Lm  | Description                      | Hours |
|-------|---|-----|----------------------------------|-------|
| 10410 | 3 | 157 | Stainless Steel LED Ground Light | 50000 |
| 10411 | 6 | 300 | Stainless Steel LED Ground Light | 50000 |
| 10412 | 9 | 580 | Stainless Steel LED Ground Light | 50000 |

<sup>1</sup> Exceeds EU standard of 70 for Lumens Maintenance Ratio

<sup>2</sup> Exceeds EU standard of Ra 80 for Colour Rendering Index

<sup>3</sup> Subject to terms & conditions (Contact Customer Service)

