



LED Amenity Bulkhead

- Ideal for all amenity applications
- Polycarbonate shatterproof construction
- Up to 50% Energy Saving
- Square/Round versions
- Clear/Opal finish available
- IP65
- 20mm Conduit entry
- Suitable for BESA box entry
- 3 year guarantee (Excluding Battery)³
- 20mm side & rear entry conduit



9W 16W **44%** Energy Saving

14W 28W **50%** Energy Saving



Emergency versions must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty.

Code	W	Description	lm	Temp	Hours
10810	9	9W Utilita LED Bulkhead, Round - Black w/Clear Bezel	900	4000	30000
10811	9	9W Utilita LED Bulkhead, Round - White w/Clear Bezel	900	4000	30000
10812	9	9W Utilita LED Bulkhead, Round - Black w/Opal Bezel	900	4000	30000
10813	9	9W Utilita LED Bulkhead, Round - White w/Clear Bezel	900	4000	30000
10826	14	14W Utilita LED Bulkhead, Round - Black w/Clear Bezel	1500	4000	30000
10827	14	14W Utilita LED Bulkhead, Round - White w/Clear Bezel	1500	4000	30000
10828	14	14W Utilita LED Bulkhead, Round - Black w/Opal Bezel	1500	4000	30000
10829	14	14W Utilita LED Bulkhead, Round - White w/Opal Bezel	1500	4000	30000
10830	14	14W Utilita LED Bulkhead, Round Emergency - Black w/Clear Bezel	1500	4000	30000
10831	14	14W Utilita LED Bulkhead, Round Emergency - White w/Clear Bezel	1500	4000	30000
10832	14	14W Utilita LED Bulkhead, Round Emergency - Black w/Opal Bezel	1500	4000	30000
10833	14	14W Utilita LED Bulkhead, Round Emergency - White w/Opal Bezel	1500	4000	30000
10834	14	14W Utilita LED Bulkhead, Square - Black w/Clear Bezel	1500	4000	30000
10835	14	14W Utilita LED Bulkhead, Square - White w/Clear Bezel	1500	4000	30000
10836	14	14W Utilita LED Bulkhead, Square - Black w/Opal Bezel	1500	4000	30000
10837	14	14W Utilita LED Bulkhead, Square - White w/Opal Bezel	1500	4000	30000
10838	14	14W Utilita LED Bulkhead, Square Emergency - Black w/Clear Bezel	1500	4000	30000
10839	14	14W Utilita LED Bulkhead, Square Emergency - White w/Clear Bezel	1500	4000	30000
10840	14	14W Utilita LED Bulkhead, Square Emergency - Black w/Opal Bezel	1500	4000	30000
10841	14	14W Utilita LED Bulkhead, Square Emergency - White w/Opal Bezel	1500	4000	30000



¹ Exceeds E.U. standard of 70 for Lumens Maintenance Ratio
² Exceeds EU standard of RA80 for Colour Rendering Index
³ Subject to terms & conditions (Contact Customer Service)



Technical Specification

Data	
Construction	Polycarbonate Body and lens
Driver	BELL
LED Chip	Samsung
IP Rating	IP65
Operating Temp	-20°C to +35°C / Emergency version minimum temperature -5°C
Input Voltage	220 - 240V
Power Factor	> 0.9
CRI	85 - Exceeds EU standard of Ra 80 for Colour Rendering Index
LMR	80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio

* All BELL Lighting luminaires are rated L80 B10, so for a 50,000 hour product. L80B10 at 50,000 hours our fittings will still have 80% of initial lumen, only 10% of fittings will fail to achieve this.

