




LED Bulkhead

- The smart replacement for 28W 2D Fittings
- Integral motion sensor options
- No lamp replacement
- No maintenance
- Opal diffuser
- 35000 hour life
- Ø300 mm x 101 mm
- Sealed durable fitting
- Suitable for BESA box entry
- 25mm side & rear entry conduit



13W  Energy Saving **53%**



Code	W	Description	lm	Temp	Hours
10883	13	Aqua3 LED Bulkhead Standard Version On/Off (No Sensor)	1200	4000K	35000
10887	13	Aqua2 LED Bulkhead Standard Version On/Off (No Sensor) Emergency 3 hour maintained	1200	4000K	35000
10991	13	Aqua3 LED Bulkhead Microwave Version On/Off With Presence Detection	1200	4000K	35000
10895	13	Aqua3 LED Bulkhead Microwave Version On/Off With Presence Detection Emergency 3 hour maintained	1200	4000K	35000





Technical Specification

Data	
Construction	Polycarbonate Body and lens
Driver	BELL
LED Chip	Samsung
IP Rating	IP65
Operating Temp	-20°C to +35°C
Input Voltage	220 - 240V
Power Factor	> 0.9
CRI	85 - Exceeds EU standard of Ra 80 for Colour Rendering Index
LMR	80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio

* All BELL Lighting luminaires are rated L80 B10, so for a 50,000 hour product. L80B10 at 50,000 hours our fittings will still have 80% of initial lumen, only 10% of fittings will fail to achieve this.

10883 13W



¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio
² Exceeds EU standard of RA 80 for Colour Rendering Index
³ Subject to terms & conditions (Contact Customer Service)